

11269-76

11269-76

Alloyed universal structural high-grade rolled steel plates and wide strips
for special purposes. Specifications

09 8100

01.01.78

11
(. . . 3).

1.

1.1.
—
—
.).
(. . . 2, 3).

1.2.
: 1; 2; 3; 4; 5.
(. . . 2).

2.

2.1.

1

	,	
:	4-60 4-5	25 . . (. 12 2 12 2 . 12 2 1 12 2 . 19 2 . 19 2 . 21 2 . 21 2 . 23 2 . 23 2 .
-	6-40	2

4

10
(. . . 3).

©
©

. 1989
, 2002

2.2. , , ()
 :
 19903 () —
 19904 () —
 82 () —
 2.2. (, . 3,).
 2.3. (). , . 1.
 1

4.0 • 8.0 • 10	5.5
• 8.0 • 10	±0.30 ±0.35 + 0.5 -0.4

2.4. 19904 () 19903

1000	2000	, 19903—74	30	4.5
	()			2.
	2000	19903-74/	-2-	/1269- 76
				2000
25	4,	() ()	()	19904—90.
	2000	19904-90/25	-4-6	11269- 76
400		82—70.	().	10
	— — 100	82 — 70/12 2	- 3	11269-76

1000	2000	, 19903—74.	30	4.5
	()			2.
	2000	19903-74		
	30	—2—		11269-76
(, . 2, 3,)		

3.

- 3.1. , , 1).
 (, . 1).
 3.2. , . 2). 11268.
 (, . 2).
 3.3. ()
- 3.4. , ().
 3.5. ,

19903 —
19904 —

)

(3.6.

).

3).

30

(

(

3.7.

3.8.

3.9.

2.

2

	1	2	3	4	5
()	+		+		+
()	—	—	—	1	4-
	—				

11

« 1 »

«—»

(3.10.

3).

1. 3 5-

2. 3. 4 5-

. 3.

3

	* / * /	%. % %			
		«5	40		
25	490-690 (50-70)	21	17	4.9—4.2	149-207
30	490-740 (50- 75)	20	16	4.8-4.1	156-217
2 (30)	490-830 (50-85)	19	15	4.7—4.0	163-229
12 2	490-740 (50-75)	15	11	4.8-4.1	156-217
12 2	490-740 (50-75)	15	11	4.8-4.1	156-217
12 2 1	490-740 (50-75)	15	11	4.8-4.1	156-217
12 2	490-740 (50-75)	15	11	4.8-4.1	156-217
19X211	490-740 (50-75)	18	16	4.8-4.1	156-217
19 2	490-740 (50-75)	18	16	4.8-4.1	156-217
21 2	490-740 (50-75)	15	11	4.8-4.1	156-217
21 2	490-740 (50-75)	15	11	4.8-4.1	156-217
23 2	490-780 (50-80)	17	15	4.6-3.9	170-241
23 2	490-780 (50-80)	17	15	4.6—3.9	170-241

1.

49 / " (5 / -)

2.
 18 30 — 1 %.
 2 .%. 30 .
 3. 19 2 . 19 2 . 21 2 . 21 2
 4 . 4 . 4 .
 (, . 1, 2).
 3.11. (, .
) 4 5- (, .
 , . 4.
 4.

					5. % * / (/ 3)	KCU. / 2 (-) /		
			()					
	pa.'		pa.'					
25	880		470—550		1030 (105)	10 49 (5.0)		
30	880		480-570		1080 ()	9 49 (5.0)		
(30 2)	900	»	200-300		1570 (160)	9 59 (6.0)		
12 2	910	»	490-550		1030 (105)	10 59 (6.0)		
12 2	910	»	490-550	»	1030 (105)	10 59 (6.0)		
12X211 1	910		500-550		980 (100)	59 (6.0)		
12 2	910		500—550		980 (100)	59 (6.0)		
19 2	925		450-550		(115)	9 39 (4.0)		
19X211	925		450-550		(115)	9 39 (4.0)		
21 2	925	»	550—570		(115)	9 39 (4.0)		
21 2	925	»	550—570		(115)	9 39 (4.0)		
23 2	890	»	590-620		(115)	9 39 (4.0)		
23 2	890	»	590-620		(115)	9 39 (4.0)		

II :
 1. + 15 . . 4.
 2. 2 1 1984 .
 (. . 1. 2. 3).
 3.12. , , , ,
 , , , ,
 (3).
 3.13. , , , ,

30

50.2.009—94.

.6 11269-76

5.5.

1. 3 5- —

)—

1763;

(5.6. . . . 3).

7564 (l).

5.7.

1497

4 = 5.65 / ^.

/_{rt} = 11,3

9454

1 3.

5

(5.8. . . . 1. 3).

1763

5.9.

9012

5.10.

50

5.11.

5639.

5.12.

120

14019.

6.

6.1.

— 7566

(6.1.1. . . . 2).

10

6.1.2.

6.1.3.

24597.

(6.1.4. . . . 3).

14192

6.1.5.

15846.

6.1.6.

10 — 1250

6.1.3. — 6.1.6. (

2).

6.2.

1.

. . , - , : . . ; . . ; . . ; . . ;

2.

24.12.76 2845

.3 ,
 (8 12.10.95)

:

	,

3. 11269-65

4. -

8.326-89	5.2
82-70	2.2; 2.4
162-90	5.2
166-89	5.2
427-75	5.2
1497-84	5.7
1763-68	5.5: 5.8
2216-84	5.2
5378-88	5.2
5639-82	5.11
6507-90	5.2
7502-98	5.2
7564-97	5.6
7565-81	4.3; 5.1
7566-94	4.5: 6.1: 6.1.3
9012-59	5.9
9454-78	5.7
11268-76	3.2
12344-88	5.1
12345-2001	5.1
12346-78	5.1
12347-77	5.1
12348-78	5.1
12349-83	5.1
12350-78	5.1
12351-81	5.1
12352-81	5.1
12353-78	5.1

12354—81	5.1
12355-78	5.1
12356-81	5.1
12365-84	5.1
14019-80	5.12
14192-96	6.1.4
15846-79	6.1.5
18895-97	5.1
19903-74	2.2; 2.4; 3.5; 5.2
19904-90	2.2; 2.4; 3.5; 5.2
24597-81	6.1.3
26877-91	5.2
28473-90	5.1

5.

(2—93)

6. 1987 ., (1996 .(2002 .) 1-83, 11-87, 8-96), 1, 2. 3, (4-2001) 1982 .,

.//.If < . <
//.

02354 оi 14.07.2000. 04.02.2002. . . . 1.40. .- . . 0.75. 233 > . 4316.

.157.

II . 107076 .. 14.

<http://Www.standards.ru> e-mail: info@astandards.ru

. " ". 103062 .. 6
0X0102