

12447-80

**Hydraulic and pneumatic drives and lubricating systems.  
Standards diameters**

12447—47

41 4000

4980 . 2845

17

01.07 198001.01 1990

1.

( , , , -  
) , , , -  
- , , , -  
- , , , -  
- , , , -  
- , , , -  
- , , , -

2.

| 1,0 | 5,0  | —  | 20 | 45  | 100 |
|-----|------|----|----|-----|-----|
| —   | —    | —  | 25 | 56  | 125 |
| —   | 6,0  | 14 | 32 | 70  | —   |
| —   | —    | —  | —  | —   | 160 |
| 2,0 | 8,0  | 18 | 40 | 90  | —   |
| —   | —    | —  | —  | —   | 200 |
| 2,5 | 10   | 22 | —  | 110 | —   |
| —   | —    | —  | 50 | —   | 250 |
| 3,0 | 12   | 28 | —  | —   | —   |
| —   | —    | —  | 63 | 140 | —   |
| 4,0 | —    | 36 | —  | —   | 320 |
|     | 16 1 | —  | 80 | 180 | —   |

1981 .

|     |      |     |  |     |  |
|-----|------|-----|--|-----|--|
|     |      | -   |  | -   |  |
| 400 | 1000 | 220 |  | 450 |  |
| 500 |      | 280 |  | 560 |  |
| 630 |      | 360 |  | 710 |  |
| 800 |      |     |  | 900 |  |

3.  
Ra20  
4.

1000

6636—69.

5.

1.  
, — 17752—72.  
2. 20765—75.