

**13824-80**

**13824-80**

Positive-displacement hydraulic drives, pneumatic actuators  
and lubricating systems. Nominal capacity per revolution.

41 4000

**01.07.80**

1.

3

:

2.

1,00	10,0	—	100	—	1000	—
—	—	11,2	—	112	—	1120
1,25	12,5	—	125	—	1250	—
—	—	14,0	—	140	—	1400
1,60	16,0	—	160	—	1600	—
—	—	18,0	—	180	—	1800
2,00	20,0	—	200	—	2000	—
—	—	22,4	—	224	—	2240
2,50	25,0	—	250	—	2500	—
—	—	28,0	—	280	—	2800
3,20	32,0	—	320	—	3200	—
—	—	36,0	—	360	—	3600
4,00	40,0	—	400	—	4000	—
—	—	45,0	—	450	—	4500
5,00	50,0	—	500	—	5000	—
—	—	56,0	—	560	—	5600
6,3	63,0	—	630	—	6300	—
—	—	71,0	—	710	—	7100
8,00	80,0	—	800	—	8000	—
—	—	90,0	—	900	—	9000

:

1.

2. 01.01.95

0°

1.2.(

1).

3.

1 3

R 20

8032,

R 10,

9000

3 —

R 10.

4.

3 ±3%.

2

5.

1. — , ,  
2. — 17398 17752.  
3. — 17398.  
4. — 17752.

1.

2.

17.06.80 2849

3.

13824- 68

4.

,	,
8032-84 17398-72 17752-81	3

5.

21.04.88 1102

6.

( 1999 )

1,

1988 .( 7—88)

. N° 021007 10.08.95. 28.12.99. 04.02.2000. . . 0,47. - . 0,30.

121 . 4315. . 87.

, 107076, , . 14.

— . “ ”, 103062, , . 6,  
N° 080102