



**14058—68**

14058.68\*

Vane pumps. Ranges of basic parameters

41 4120  
41 4272

20            1968 . 9 135

1969 .

12446—80

13824—80.

12445—80,

1

/ <sup>2</sup>	63	100	125	(140)	160	200
/	6,3	10,0	12,5	( ,0)	16,0	20,0

2

/	600	750	960	1500	1920	2400	3000	3780	4800	6000
/	10,0	12,5	16,0	25,0	32,0	40,0	50,0	63,0	80,0	100,0

1. ( , . . 1).  
2.

\* 1980 . 1980 . ( 12 1980 . ).

$V_0$  <sup>3</sup>

	-		-		-		-
1,00	—	10,0	—	300	—	1000	—
—	•—	—	11,2	—	112	—	1120
1,25	—	12,5	—	125	—	1250	—
—	—	—	14,0	—	140	—	—
1,60	—	16,0	—	160	—	—	—
—	—	—	18,0	—	180	—	—
2,0-0	—	20,0	—	200	—	—	—
—	—	—	22,4	—	224	—	—
2,50	—	25,0	—	250	—	—	—
—	—	—	28,0	—	280	—	—
3,20	—	32,0	—	320	—	—	—
—	—	—	36,0	—	360	—	—
4,00	—	40,0	—	400	—	—	—
—	—	—	45,0	—	450	—	—
5,00	—	50,0	—	500	—	—	—
—	—	—	56,0	—	560	—	—
6,30	—	63,0	—	630	—	—	—
—	—	—	71,0	—	710	—	—
8,00 •	—	80,0	—	800	—	—	—
—	9,00	—	90,0	—	900	—	—

1.

2.

±3%.

(

, . . 1).

. 28.05.81 , . J9.08.81 0,25 . . 0,13 . . . . . 6000 3 . .  
 « \ » , , , -557, , . . , 12/14. . 2456 . . 3.