



14059—68

Piston pumps.  
Ranges ! basic parameters

14059-68\* \*

41 4140, 41 4150, 41 4160, 41 4170, 41 4274, 41 4275

20 1968 ' 135 -  
01.07. 69

. 1—3.  
12446—80 13824—80. 12445—80,  
I

/ ²	63	100	160	200	250	320	400	500	630
	6,3	10,0	16,0	20,0	25,0	32,0	40,0	50,0	63,0

2

«

/	300	378	480	600	750	960	1500	1920	2400	3000	3780	4800	6000
/	5,0	6,3	8,0	10,0	12,5	16,0	25,0	32,0	40,0	50,0	63,0	80,0	100,0

. 1. -  
-

\* 1982 . 1,  
1980 . ( 12—80).

0 3

	-		-		-		-
<b>1,00</b>	-	<b>10,0</b>		<b>100</b>	-	<b>1000</b>	-
-	-	—	,2	-	<b>112</b>	—	<b>1120</b>
<b>1,25</b>	-	<b>12,5</b>	-	<b>125</b>	-	<b>1250</b>	-
-	-		<b>14,0</b>	-	<b>140</b>	-	<b>1400</b>
<b>1,60</b>	-	<b>16,0</b>	-	<b>160</b>	-	<b>1600</b>	-
-	-	·	<b>18,0</b>	-	<b>180</b>	-	<b>1800</b>
<b>2,00</b>	-	<b>20,0</b>	-	<b>200</b>	-	<b>2000</b>	-
-	-	—	<b>22,4</b>	-	<b>224</b>	-	-
<b>2,50</b>	-	<b>25,0</b>	-	<b>250</b>	-	-	-
—	-	—	<b>28,0</b>	-	<b>280</b>	-	-
<b>3,20</b>	-	<b>32,0</b>	-	<b>320</b>	-	-	-
-	-	-	<b>36,0</b>	-	<b>360</b>	—	-
<b>4,00</b>	-	<b>40,0</b>	-	<b>400</b>	-	—	-
-	-	-	<b>45,0</b>	-	<b>450</b>		-
<b>5,00</b>	-	<b>50,0</b>	-	<b>500</b>	-	—	
-	-	-	<b>56,0</b>	-	<b>560</b>	—	
<b>6,30</b>	-	<b>63,0</b>	-	<b>630</b>	-	—	
-	-		<b>71,0</b>	-	<b>710</b>	—	
<b>8,00</b>	-	<b>80,0</b>	-	<b>800</b>	-	-	
-	<b>9,00</b>	-	<b>90,0</b>	-	<b>900</b>	-	

:

1.

-

2.

-

±8%.

( , . 1).

. 01.03.S3 . . 11,04.83 0,25 . . 0,16 .- . . . 4000 3 .  
 « » , , -557, , 12/ . , 1667” . 3.