



14060—68

Gear hydraulic motors.
Ranges of basic parameters

14060-68*

41 4210
41 4271

20 1968 . 135

01.07.69

. 1—3.

12446—80 13824—80.

12445—80,

1

/>

/ 2	25	63	100	(140)	160	200
	2,5	6,3	10,0	(14,0)	16,0	20,0

2

«

/	/	/	/	/	/
-	-	6 0 0	10,0	6000	100
—		750	12,5	—	—
-	-	960	16,0	—	—

* (1986 .)
1980 . (12—80).

. 2

/	/	/	/	/	/
120	2,0	1200	20,0		
150	2,5	1500	25,0	-	-
192	3,2	1920	32,0	-	-
240	4,0	2400	40,0	-	-
300	5,0	3000	50,0	---	-
378	6,3	3780	63,0	-	-
480	8,0	4800	80,0	-	-

3

*

	-		-		-		-
1,00		10,0		100	-	1000	
			11,2		112		1120
1,25		12,5	.	125		1250	-
-	-	-	14,0	-	140	-	1400
1,60	-	16,0	-	160		1600	
			18,0	-	180		1800
2,00		20,0	-	200		2000	
			22,4	-	224		2240
2,50		25,0		250		2500	
		.	28,0		280		2800
3,20		32,0		320		3200	
.			36,0		360		
4,00		40,0		400			
			45,0		450		
5,00		50,0		500			
-		-	56,0	-	560	-	

	-		-		-	.	-
6,30	-	63,0		630	-	-	-
-	-	-	7101	-	710		-
8,00	-	800	-	800		-	-
-	9,00	-	90,0	- j 900		-	-

1.

2.

±3%

(

08 10 86

14 11 86 0,25

0,25
4000

-
3

0,21

« » , 123840,
 , . 3 , 12/14 4729