

**14061—68**

.

**3**

Gate hydraulic motors. Ranges of basic parameters

14061-68\*

41 4220, 41 4272

20 1968 . 135

01.07.69

. 1—3.

1

/ 3	63	100	J25	140	160	200
	6,3	10,0	12,5	(14,0)	16,0	20,0

2

/	/	/	/	/	/	/	/	/	/
0,60	0,010	6,0	0,10	—60—	1,00	600	10,0	6000	100
—	—*	--	—	75	1,25	750	12,5	—	—
0,96	0,016	9,6	0,36	96	1,60	960	16,0	—	—
-	-	—	—	120	2,00	1200	20,0	—	—
1,50	0,025	15,0	0,25	150	2,50	1500	25,0	—	—
—	—	—	-	192	3,20	1920	32,0	—	—
2,40	0,040	24,0	0,40	240	4,00	2400	40,0	—	—

\* ( 1986 . ) 1, 1980 . ( 12—80 ).

/	/	/	/	/	/	/	/	/	/
-	-	-	-	300	5,00	3000	50,0	-	-
3,78	0,063	37,8	0,63	378	6,30	3780	63,0	-	-
-	-	-	-	480	8,00	4800	80,0	-	-

0

	-		-		-		-
1,00		10,0		100		1000	-
-		-	11,2		112		1120
1,25		12,5		125		1250	-
			14,0	-	140		1400
1,60		16,0		160		1600	
		•	18,0		180		1800
2,00		20,0		200		2000	
			22,4		224		2240
2,50		25,0		250		2500	
			28,0		280	•	2800
3,20		32,0		320		3200	
			36,0		360		•
4,00		40,0		400	-		-
			45,0		4 5 0		-
5,00	•	50,0		500			-
			56,0		560		•
6,30		63,0		630	>		-
			71,0		710		-
8,00		80,0		800			-
•	9,00		90,0	-	900		

1. : -
2. .  
±3%.
- ( , . 1).

. 3      14061—68

12446—80      13824—80.      12445—80,

. 08,10.86      . 18.11.86 0,25      . . . 0,25      . .- . 0,16      .- . .  
6000      3      .  
«      »      ,123840,      ,      ,  
., .3.      ,      , 12/14,      . 4730,