



14062—68

Piston hydraulic motors. Ranges of basic parameters

14062.68*

41 4240, 41 4250, 41 4200, 41 4274, 41 4275

20 1968 . 135

01.07.69

—
,
1—3.
—
12445—80,
12446—80 13824—80.
1

/?

. / ²	63	100	160	200	250	320	400
	6,3	10,0	16,0	20,0	25,0	32,0	40,0

2

/	/	/	/	/	/	/	/	/	/
0,60	0,010 j	6,0	0,10	60	1.00 l	600	10,0	6000	100
—	— [—	—	75	1,25	750	12,5	—	—
0,96	0,016	9,6	0,16	96	1,60 !	960	16,0	1 —	—

^

*

{

1986 .)

1980 . (1,
12—80),

		10,0	—	100	—	1000	—	10000	—
1	I	—	11,2	—	112	—	1120	—	11200
		12,5	—	125	—	1250	—	12500	—
1	I	—	14,0	—	140	—	1400	—	14000
>		16,0	—	160	—	1600	—	16000	—
1	I	—	18,0	—	180	—	1800	—	18000
		20,0	—	200	—	2000	—	20000	—
1	I	—	22,4	—	224	—	2240	—	22400
		25,0	—	250	—	2500	—	25000	—
1	I	—	28,0	—	280	—	2800	—	28000
io	I	32,0	—	320	—	3200	—	32000	—
1	I	—	36,0	—	360	—	3600	—	—
4*		40,0	—	400	—	4000	—	—	—
1	I	—	45,0	—	450	—	4500	—	—
0	I	50,0	—	500	—	5000	—	—	—

IIIIIIIIIIIIIIIIIIII

-

-

-

-

-

X
£
t
*3
2
>
3
&
m
&
m

CV

1	* 00	1	2,40	1	1,50	1	« a
1		1 L	4*	1 1	to	1 1	*
1		1		1			£ a a
1		1 1		1 1		1 1	0\
00			N3	to	1-^	1- to	s a
00)		4^	>	to	to	\
00	00		to 4^	to		1- to	0V £
00	05		4^	to	to	to	o'
1	1 j	[i 1	1	1	1	1	0 s' a

pv

£
S3
V
0
1
£
*
S
J
D
a

0
1
a
2
?
?
N3

0
3
8
1
\$
4
•

V_0 3

	—	—	56,0	—	560	·	5600	—	·
6,30		63,0		630		6300			
		—	71,0	—	710	—	7100		
8,00		80,0		800		8000	—		
—	9,00		90,0	—	900		9000	·	

1.

2.

±3%.

(, . 1).

. 0S.10.86

. 16.12.86 0,25

4000

. 0,25
3

. - . 0,21

- .

« »

, 123840, , ,
, . 3. , 12/14. . 4731.