

14118-85

1-96

14118-85

Wire from precision alloys for elastic elements.
Specifications

12 6600

01.07.86

1.

1.1.

— — ;
— ;
— — ;h8, h9, 0, 1;
js 8, js 9, js 10, js ;

3 6 XT 40 :

— ;

(1.2. , . 2).

. 1.

©
©, 1985
, 1997

1

		,
40		0,1-6,0
40		
36		
36	5	,3-5,0
42		
36	8	0,5-5,0
44		0,2-7,0

1.3.

2771.

1.4.

2771

0,30

0,32 2,0

R40

h8, 9 j_s8, j_s9;h9, 0 j_s9, j_s10;hi 1]₅11.

1.5.

j_s10,

40

0,5

h9,

0,5-j_s 10- - -40

14118-85

36

0,3

(

0,3- 9- -36

14118-85.

2).²

2.

2.1.

2.2.
10994.

2.3.

6,0

6,0

—

3 14118-85

2 4

, ,

, , , , ,
,

(2 5 , . 1).

2 6

, , , , 2.
(2 7 , . 2).

3
(2 8 , . 1, 2).
36 , 36 5 , 42 , 44 0,6

2 9

, 6,0 ,

,
40 0,5
1960 / 0,02 , / 2)
40 40 0,6
(40 0,5)

(, . 2).

		* / 2(/ 2)		
40	0,10 0,50 0,53 1,0 1,0	1340(137) - 1670(170) 1210(130) - 1570(160) 1080(110) - 1470(150)	1520(155)- 2160(220)* 1420(145) - 2060(210)* 1320(135) - 2060(210)*	200 200
40	0,3 5,0		1470(150)	1890(193)
36 5	0,3 5,0	1080(110)	1150(117)	
36	0,3 5,0	980(100) - 1270(130)	1180(120) - 1670(170)	—
36 8	0,5 5,0	1080 (110) ~	1370(140)	—
42	0,3 5,0	980(100)	80(110)	—
44	0,2 7,0	980(100)	1080(110)*	—

1

36 40

2

«*»

01 07 94

36	8	-	0,3 5,0	700±10	2		<?,, / 2 (/ 2)	-	-	
		-	0,3 5,0	700±10	2		(/ 2)	oo , / 2 (/ 2)	6 ₁₀₀ , %	
42		-	0,3 5,0	600-700	1-2		1370(140)	*		
		-	0,3 5,0	600-700	1-2		1570(160)			
44		-	0,2 7,0	600-700	1-2		-			
		-	0,2 7,0	600-700	1-2		1270(130)			
		1 2	, 8	*		01 07 94 3,0	40	, 36	, 36	
							3,0		5 , 6	

2 10

,

14117

3.

3 1

, ,

3 2

— 100 %

(,),

— 1

,

— (,),

6,0

3 3

,

—

7566 4

4.

4 1

, 6507, 11358

,

4 2

12345,	12346,	12347,	12348,	12344,
12350,	12351,	12352,	12353,	12349,
12355,	12356,	12357,	12361,	12354,
				28473

— , 7565

4 1, 42 (

2).

4 3

—

(4 4 , . . 1).
 10446 (,)
 100
 4 5 10447
 4 6
 4 7 1778
 1 4 4
 4 8 1579

5. , ,
 5 1 , , —
 7566 , ,
 5 2 0,45 —
 0,45 —

0,45 —
 () —
 , (,) () —

, , . 2).
 (5 3 , , 45, 20, -20
 -40 20799
 5 4 , 8828, 10396,
 9569 —

| 11) , - 2991 (.
| 10396, 10354, 16272 9569, 8828,
| 14253. . .

3282

, 1200
— 180 .
5.5. — 14192.
5.6.

21650. 24597.

(5.7. , . 2).

6.

6.1.

6.2. 15

1.

2.

25.06.85 1884

3. — 5

4. 14118-69

5. -

1579-93	4.8
1778-70	4.7
2771-81	1.3, 1.4
2991-85	5.4
3282-74	5.4
6507-90	4.1
7565-81	4.2
7566-81	3.4, 5.1
8828-89	5.4
9569-79	5.4
10354-82	5.4
10396-84	5.4
10446-80	4.4
10447-93	4.5
10994-74	2.2
11358-89	4.1
12344-88	4.2
12345-88	4.2
12346-78	4.2
12347-77	4.2
12348-78	4.2
12349-83	4.2
12350-78	4.2

12351-81	4 2
12352-81	42
12353-78	4 2
12354-81	4 2
12355-78	42
12356-81	42
12357-84	4 2
12361-82	42
14117-85	2 10
14192-77	5 5
14253-83	54
16272-79	54
20799-88	5 3
21650-76	56
24597-81	56
28473-90	42

6. 08.07.92 659

7. (1997 .) 1,2, -
1990 ., 1992 .(6—90, 9—92)

021007 10 08 95 12 03 97 02 04 97
0,70 - 0,65 205 362 256

107076, , , 14

— “
, 6 ”