



17019—78

Fixing parts for pipelines and cables.  
Specifications

**I7019-78**

01.01.79  
01.01.94

( , . . 2).

1.

1.1.

)

( —

1.2.

(

2).

, 1988

1.3. ( , . 2).  
 1.4. ,  
 16 ,

16 , 21631—76.

8 ,

HV 5/15—418 -509.

1.5.  
 . 2.

2\*

10, 20, 25, 08 ,	21.	15. 15.
8	.	136—41 10834—76
12 17 9 4 12 18 ,	.	.
16 ; 1	.	/

\* . 1 , . 2.

8

9.301—86.

8

( , . 1, 2).  
 1.6.

: 15, /<sub>s</sub> 15, ±—— . | 15

( , . 1).

1.7.

: /<sub>s</sub> 16, :<sub>s</sub> lo, = ——— .

( , . 1).

1.8.

. 3.

3

0,5	5,0
0,5	$\pm 0,2$
5,0	$\pm 0,5$
	$\pm 1,0$

1.9.

 $\pm 0,5$ 

1.10.

0,5

1.11.

1.12.

1.13.

1.14.

9150—81.

16093—81.

2.

2.1.

26964—86.

2.2.

500

2.1, 2.2. (

2).

2.3.

2.4.

10%

3

2.5.

2.4, 2.5. (

2).

### 3.1.

( )

3.2.

### 3.3.

2999-75

2  
1497-84.

3.4.

9.302—79.

4.

## 4.1.

## 4.2.

12301—81.

9569—79,

$$\begin{array}{r} -4 \\ 10354 - 82 \end{array}$$

9327—60,  
4.3.

74X52

(  
4.4.

5959—80  
2991—85.

1).

515—77

7376—84,

3560—73.

35  
4.5.

(  
4.6.

1, 2).

4.7.

(  
3 «

—

14192—77.

».

2).

4.8.

—

,

,

,

,

,

4.9.

4.10. ( , . . . 2).

4.10. ( )

4.11. ) ( 3 , . . . 2).

5.

5.1.

,

,

5.2.

12 18 10 — 14,5

,

— 11

08	, 10, 20, 25, 155° );	223,15	428,15	(	50	
	,	1			15150—69	
	;					
	,	2, 3, 4			15150—69	
	15.				4	
	15150—69		15.	;		
	,	7. 8			15150—69	
	21.					
8	150° );	293,15	423,15	(	20	
	,	1			15150—69	
	;					
	,	2, 3, 4			15150—69	
	;					
	,	1			15150—69	
	.	.	.	.	136—41	
	10834—76					
1	155° );	123,15	428,15	(	150	
	308,15 (35° );		98%			
	133,3-10~?					
16	100° );	77,15	373,15	(	196	
	308,15 (35° );		98%			
	133,3-10~8					
63	200° );	20,15	473,15	(	253	
	308,15 (35° )		98%			
-4	200° );	213,15	473,15	(	60	
	133,3-10~8					

610		213,15	343,15	(	60
	70° );				
				666,5	
15803—020; 20908—040; 21008—075	60° )	233,15	333,15	(	40
12X18HIOT		20,15	673,15	(	253
	400° );				
				98%	-
	308,15 (35° );				
				133,3 - 10 — <sup>3</sup>	
12 17 9 4		20,15	673,15	(	253
	400° );				
				98%	-
	308,15 (35° )				

( , . 2).

1.

. . ( ), . . , .

2.

30.01.78 280.

3. — 1992 .

4. 17019—71

5.

9.301—86		1.5
9.302—79		3.4
515-77		4.4
1497—84		3.3
2991—85		4.4
2999—75		3.3
3560—73		4 4
5959—80		4 4
7376—84		4.4
9150—81		1.12
9327—60		4.2
9569—79		4.2
10354—82		4.2
10834—76		1.5
12301—81		4.2
14192—77		4.7
15150—69		
16093—81		1.12
21631—76		1.4
26964—86		2.1

6. ( 1988 .) 1, 2, -  
1983 ., 1988 .( 7—83, 4—88).7. 1987 . 01.01.94 ( -  
14.01.88 54).

1 J.07.88 . . 04.10.88 0,75 . . 0,75 . . 0,53 . .  
9000 3 . .  
« » , 123840, , ,  
, . 3, , , 39. . 2149.