



22309—77

7-92

22309—77

Pipeline valves, Electv[^]transnvlsloivs.
Basic parameters

01.01.73

1.

2.

*

		±25\$		(,) -			
.	.	/	/			\	
5 25	0,5 2,5	0,99	9,5	6,28	1	37,68	6
				37,68	6	150,70	24
25 140	* <	1,26	12,0	6,28	1	62,80	10
				62,80	10	282,50	4(5)
		2,52	24,0	6,28	1	62,80	10
				62,80	10	282,50	45
100 300	10 30	0,63	6*0	6,28	1	37,68	6
				37,68	6	226,00	36
				1226,00	36	1256,00	200
		2,62	25,0	6,28	1	37,68	6
				37,68	6	226,00	36

©

, 1977

©

, 1993

		±2 %		(,); -			
. .		/ /					
100 250	10 25	2,62	25,0	226,00	36	1256/00	200
		5,24	50,0	6,28	1	37,68	6
				37,68	6	226,00	36
				2126,00	36	1256/00	
250 1000	25 1100	0,63	6,0	6,28	1	37,68	6
				37,68	6	226,00	36
				226,00	36	1256/00	20
		2,62	25,0	6,28	1	37,68	6
				37,68	6	226,00	36
				226,00	36	1296,00	200
		5,24	0/0	6,28	1	37,68	6
				37,68	6	226,00	36
				226,00	36	1256,00	200
1000 2500	100 250	0,63	6,	6,28	1	37,68	6
				37,68	6	226,00	36
				226,00	36	1296, 0	20(0)
		2,62	25,0	6,28	1	37,68	6
				37,68	6	226,00	36
				226,00	36	1256,100	200
		5,24	50,0	904,32	4	5024,0 ,	800
				6,28	1	37,68	6
				37,68	6	226,00	36
2500 10000	250 1000	1,05	10,0	226/00	36	1256/00	200
				904,32	144	5024,0	800
				6,28	1	37,68	6
				37,68	6	226,00	36
				2 ©,00	36	1256,00	2

(,) , . 1, 2).

\$

22300—77

J.

., . . , . . (), . .
2. , . .
100 13,01.77
3. — 1995 ., — 5
4.
5. 24.05.90 1274
6. (1993 .) 1, 2,
 1985 ., 1990 .(2—86, 8—90)

. 17.08.93. , 1(010.93. . 0.23 0.23.
 . 0.17. 1067 722.
« » , 107076, .
« » , nep. 6. , 440