

**22413-89**

Pipeline valves with electromagnetic drives.  
Main parameters

MKC 23.060.30  
37 0000

01.01.91

0,01      (0,1      /       $\frac{1}{2}$ )      20      (200      /       $\frac{1}{2}$ )      (      )       $D_y$       3      200  
                 40°      225°  
       1,0; 6,3      10      (10; 63      100      /       $\frac{1}{2}$ )       $D_y$       6, 10      15  
                 40°      175° .

1.      ,      , —      24856.  
       «      »      ,      , —      24856.  
 2.      -

$( \ / \frac{1}{2}),$	$D_y,$		
0,01 (0,1)	3, 6, 10, 15, 25, 32, 40, 50, 65, 100, 150, 200	40	60
0,1 (1)	3, 6, 10, 15, 25, 40, 50, 65, 100, 150		
0,25 (2,5)	3, 6, 10, 15, 25, 40		
0,63 (6,3)	3, 6, 10, 15, 25, 40, 50, 65	40	150
1,0 (10)	3, 6, 10, 15, 25, 40, 50	40	60
1,6 (16)	6, 10, 15, 25, 40, 50, 65, 80, 100, 125, 150	40	150
2,5 (25)	6, 10, 15, 25, 40, 50, 65, 80, 100, 125, 150	40	225
4,0 (40)	10, 15, 25, 40, 50, 65, 80, 100	40	100
6,3* (63); 10* (100)	6, 10, 15	40	175
20,0 (200)	25	40	60

\*



0,1(1)	6			15	—	1,0	
	10				20	2,5	
	15			—		4,0	
	25					7,0	
	40			40	8,0		
	50				11,5		
	65				15,5		
0,25 (2,5)	15			50	—	4,0	
	25				—	4,5	
	40					10,0	
0,63 (6,3)	10			15	—	2,0	
	25			25	—	6,0	
	40				—	12,0	
	65			350		34	
1,0(10)	6			—	11	3,5	
1,6(16)	10			20	40	2,5	
	15					2,8	
	25			350	—	18	
	50					22	
	100					68	
2,5 (25)	6			20	40	2,5	
	10					3	
	15					4,0	
	25					8,5	
	40					12	
	50			—		18,5	
	65					32	
4,0 (40)	10			15	—	3,0	
	15					6,0	

. 4

**22413-89**

1.

2.

—      **15.06.89    1610**

3.

**22413-77**

4.

,

12434-93	<b>10</b>
15150-69	
21128-83	9
24856-81	

5.