



22642—88

10—88/608

%

Pinch pipeline valves. Main parameters

22642—88

37 0000

01.01.90

* , 24856.

©

, 1989

()

(/ ²)	D			** ,
0,63 (6,3)	50	,	-	8,0
	65*			,
	80			14,0
	100			28,0
	125			32,0
	150			53,0
	200			74,0
	250			,
	300			,
1,0 (10)	10	,	-	,
	15			,
	20			,
	25			4,0
	32			,
	40			5,3
	50			,
	80			,
	100			,
	125			,
	150			,
	200			,
	250			,
	300			,
1,6 (16)	10	,	-	,
	15			,
	20			,
	25			,
	32			,
	40			,

/

(/ ²)	D_y ,			** ,
1.6 (16)	50			
	80		,	
	100		-	

*

**

,

2

, (/ ²)	D ,			$Kv - /$	$h y_t$	*
0,6 (6)	50	;	;	100	32	16,8
	80			300	48	26,2
	100			400	70	43,0
	125			900		45,0
	150			2500	120	80,0
	200			3000		
	250			5000	165	
	300			8000		
1,0 (10)	10	,	,	2,5	6	
	15			5,5	10	
	20			10	16	
	25			25	20	
	32			40	25	
	40			63	30	
	50			100	32	
	80			300	48	

						*
(/ ²)	£>,	-	-	> ®/	h_y ,	,
	100			400		
	125			900	70	
	150			2500		
1,0(10)	200	,	;	3000	120	
	250!			5000		
	300			8000	165	

*

4.

1 2,

5.

6.

7.
9544,() —
— 0,01 % Kv_Y .

1.

; . . ; , ; (); - . . ; . . ;

2.

14.11.88

3683

3.

— 1993 .
— 5 .

4.

22642—77; 9701—79 (.
). .

,	
9544—75 24856—81	7 1

16 000 . 29,11.88 . 02.01.89 0,5 . . . 0,5 . . . 0,26 . . . 3 .
« . » . , 123840, . , 6. . 3277