

24091-80

Dead tube connections.
Construction and basic dimensions

15781—70
21855—76

8


1980 . 1589

01.07 1981 .
01.07 1991 .

1.

393 (120°).
2.

233 (40°)



*

- 1— 21873—78; 2—
3— 23353—78;
23354—78

	d	°	L	” “		1000 , ,
				S	Si	
1	4	2,5	17	9	10	19
	5	3,0	18	12	12	23
	6	4,0			14	24
	!	6,0	20			28
2	6	4,0	22			30
	8	6 0	23	14	17	45
	10	8,0	2	17	19	55
	12	10,0	26	19	22	80
	16	12,0	30	24	30	145
	18	15,0	32	27	32	175
	22	20,0		32	36	230
	28	25,0	34	41	41	320
	34	32 0	39	46	50	545
	42	40,0	4)	55	60	720
3	6	3 0	26	14	17	40
	8	4,0	28	17	19	55
	10	5,0	30	19	22	80
	12	6,0	33	22	24	85
	14	8,0	36	23	27	135
	16	10,0		27	30	150
	20	,	42	32	36	245
	25	15,0	46	41	46	435
	30	20,0	50	46	50	560
		25,0	56	55	60	845

. L .

1 $d_a=8$:

1—8 24091—80

3. -

22525—77, 1.

4. , -

, , —
15763—75.

1 24091—80

26.10.89 3203

01.07.90

«and basic dimensions».

1 : « »,
: «1. 41 9300. -
24°». : *Du*;
2. (2) 12,0 32,0
: (. . 152)

(24091-80)

	<i>D</i>	<i>D</i>	<i>L</i>	« *		1000 ” ’
					Si	
2	15	12,0	30	22	27	101
	(16)			24	30	
	(34)	32,0	39	46	50	416
	35					403

« 1000 „. : 19 10, 23
 15, 24 15, 28 19, 30 24, 45 34, 55 45, 80 62, 175 139,
 230 195, 320 270, 720 626, 40 41, 55 57, 80 74, 85 96, 135
 134, 245 244, 560 564;

— 2: «2. , ,
 ».

(2 1990 .)