

24266-94

-

,

,

24266-94

1

(

)

,

2

(

Ne 6—94

21

1994 .)

:

3

,

10

1996 .

8

24266—94

4

1

1996 .

24266-80

©

, 1996

,

Reducers and motor-reducers shad ends.
Basic dimensions, allowable torques

1996—07—01

1

1:10

2

10748—79

12080—66

12081—72

23360—78

1:10.

24266-94

3 ,
 3.1 *d*
 Mj
 1.
 3.2 *dj*
 2
 3.3 —
 12080 12081.

<i>d%</i>	1 l,	rfi,	Mi.	rf ,	Mi. j	tfl,	Mi,	<i>d</i> ¥	
110	8,0	28	180	48	800	85	4500	150	25000
12	16,0	30	200	50	1000	90	5600	160	31500
14	22,4	32	250	55	1400	100	8000	180	45000
16	31,5	35	355	60	1600		11200	200	63000
18	45,0	38	400	65	2240	120	12500	—	—
20	63,0	40	500	70	2800	125	16000	—	—
22	90,0	42	560	75	3150	130	18000	—	—
125 125,0	45	710	80	4000 j	140	22400	—	—	
1				Mi					

2 ,
 3 12081 =8,0. Mi , Mi 4; 5,6 11,2. 12080
 4

2

$ rf $	Mi, ! <fc,	Mi, di,	(6, di,	Mi 1
18	31,5	250	65	1660
20	45	355	70	2000
22	63	500	75	2240
25	90	560	80	2800
28	125	710	85	3150
30	140	1000	90	4000
32	180	1400	1100	5600
				220
				63000
				1

3 , **25** /

4 **2** **—** **125**

5
3.4 — 23360, 10748,
12081.

24266—94

()

A.I .1.

		j		
60.ice		,		
18	1,0	80	— — 1	
Or 20		125	3,0	
28	1,6	130		
30		280 1	4,0	
75	2J			1

621.824.434:006.354 **21.120.10** **15** **41 8600**

21.120.10

15

41 8600

021007 10.08.95. 23.02.96. 08.05.96.
035. .035. 200 3418. 213.
107076, , „14.
— " "
, . „6