

**24982-81**

**Rolled sheet of corrosion-resistant, heatresistant  
and heat-proof alloys. Specifications**

**09 9388**

**01.01.93**

45	( 747),	58	( 795),	65	28	( 126),	32	( 670),	38	( 703),
70	( 652),	75	( 602),	78	( 567),	65	( 760),	67	( 202),	
				70	-	( 435),	77	-	-	
28	-	( 126- ),	38	-	( 814 - );		-	( 202- )	-	
			70	-	( 652- ).				-	

( , . 1).

**1.**

**1.1.**

— 1, 2, , 4,  
— 16, 26, 36 46;

**2.**

2.1.				1000			32
( 650)—		1200	,				
	:	2,0	11,0	—	, 0,8	3,9	—
2,0		.11	20	,		0,5—0,7	.
2.2.	,	—	19903				:
	—	—	19904				
2.3.						.1.	

			1	,
	( / <sup>2</sup> )	3,9	4	
680 (70)		15	12	12
. 680 (70) 830 (85)			15	15
. 830 (85) 1030 (105)		20	20	20
. 1030 (105)		25	30	25

12—20

(  
2.3.1.  
75 ( 602) 38 ( 703) 10 1 .

65 , 36,  
6x1000x2000:  
-----  
0-6x1000x2000 19903-74  
-----  
65 —36 24982-81

78 , 2 ,  
2x710x1600:  
-----  
- 0-2x710 1600 19904-90  
-----  
78 —2 24982-81

## 3.

3.1.

5632.

3.2.

3.3.

11

, . 11

11

3.4.

3.5.

3,9

. 2.

				/ <sup>2</sup> ( / <sup>2</sup> )	/ <sup>2</sup> ( / <sup>0,2</sup> )	6, %
28 ( 126), 28 - ( 126- )	1080-1140	20	930 (95)			35
		900	165(17)			30
32 ,( 670)	1100-1150	20	470 (48)	195 (20)		25

. 2

	, °	, °				
			/ <sup>2</sup> ( / <sup>2</sup> )	/ <sup>2</sup> ( / <sup>2</sup> )	6 <sub>5</sub> , %	
			0 <sup>2</sup> ,			
38 ( 703), 38 - ( 703- )	1060-1140	20	800 (82)	35 40		
	1080-1100	800	185(19)			
45 ( 747)	1060-1100	20	590 (60)	30		
58 ( 795)	1050-1090		740 (75)	345 (35)	35	
65 ( 567)			830 (85)	390 (40)	40	
67 ( 202), 67 - ( 202- )	1070-1090		930 (95)	15 —		
	, (850±20) " , 5 ,					
70 ( 652)	1100-1150	20	980 (100)	30		
		900	100 (10)	25		
70 - ( 652- )		20	980 (100)	30		
		900	100 (10)	40		
75 ( 602)	1050 1080	20	900 (92)	40		
		800	245 (25)	45		
78 ( 435)	980 1020	20	860 (88)	35		
		800	175(18)	45		
77 ( 437 )	1080-1120	20	930 (95)	20		
		750	590 (60)	8		
( 202- ) 77 ( 437 ),			67 ( 202), 67 -			

1.

2.

( 202- ) 77 ( 437 ),

3.6.

67 ( 202), 67 -

4

3.

					/ $^2$ ( / $^2$ )	/ $^2$ ( $^0$ / $^{2+}$ )	$6_5$ , %	
28	- ( 126- )	1080-1140	20	930 (95)		175(18)	25	
			900	195 (20)			40	
32	( 670)	1080-1120	20	490 (50)		410 (42)	30	
38	( 703),	1120-1140		830 (85)			35	
38	- ( 703- )	1080-1100	800	185 (19)		440 (45)	40	
45	( 747)	1060-1100		590 (60)			30	
58	( 795)	1050-1090		740 (75)	390 (40)	35		
65	( 567)			850 (87)		410 (42)	40	
65	( 760)			830 (85)			35	
67	( 202),	1140-1160		930 (95)	550 (56)	18		
67	- ( 202- )							
70	- ( 814 - )	1050-1090		780 (80)	365 (37)		40	
75	( 602)	1050-1080		930 (95)				
78	( 435)	980-1020	20	245 (25)		440 (45)	30	

1.

2.

( 202- )

3.

65 ( 567)

67 ( 202), 67 -

(1100+20) ° .

3.7.

3.8.

6—10 —  
( 602) 78 ( 435);  
5—10 —  
28 - ( 126- );

3,9

38 ( 703), 75

4.

	,			
1			,	,
1			,	,
2		-	,	,
26	,	,	,	2
			,	
36			,	
4		-	,	,
46	,	,	,	

1.

,

2.

,

3.

4.

5.

25

3647.

70 - ( 652- ) , 77 — ( 437 ) 38 - ( 703- ); 3,9 70 ( 652),  
 5 — 4 38 ( 703),

75 ( 602) 78 ( 435).

3.9.

3,9

180°

32 ( 670)

70 ( 652),

38 ( 703),

3.10.  
 ( 814 - ),

65 ( 567), 65 ( 760), 70 -  
 78 ( 435)

78

( 435)

3.11.

67 ( 202,

202- )

18 %

40 / 2(4 • / 2).

3.12.

70 - ( 814 - )

220

3.13.

-

6

4.1.

7566

4.2.

4.3.

6032;

1778;

4.4.

7566.

## 5.

5.1.

7565.

5.2.

5.3.

19903,

19904

26877.

6507,

—

7502,

427

(

1).

7564

5.5.

(20°) °

3,0

1497,

3,0

11701

 $f_0 = 5,65 / F_0$ .

3,0

5,65  $F_0$  $g = 20$ 

—

9651

 $f_0 = 5,65$

5.6.		9454.	
5.7.			1778.
5.8.		5639.	
5.9.		9012.	
5.10.	—	14019.	
5.11.	,	.34,	
5.12.		(800+10) °	
		30 ,	
			—
			.5.

5

65 ( 567) 65 ( 760)	263 <sup>3</sup> 4204, <sup>40</sup> 9485 1000 <sup>3</sup>	( 1,835 / <sup>3</sup> )	- 48
70 - ( 814 - )	1200 <sup>3</sup> 3118 1000 <sup>3</sup>	( 1,179 / <sup>3</sup> )	200
78 ( 435)	335 <sup>3</sup> 4204, 268 <sup>3</sup> 1,339 / <sup>3</sup> )	( 1,835 / <sup>3</sup> )	96

6032.

6. , , ,

6.1. , , ,	7566
6.1.1. , , ,	
6.1.2. , , ,	14192
6.1.3. , , ,	24597.
6.1.4. , , ,	3560, 6009
21650.	
6.1.5. , , ,	— 1250
80 .	
6.1.6. , , ,	
6. ( , , . 1).	

1.

2.

19.10.81    4595

3.

427-75	5.3	7565-81	4.3, 5.1
1497-84	5.5	7566-94	4.1, 4.4, 6.1
1778-70	4.3, 5.7	9012-59	5.9
3118-77	5.12	9454-78	5.6
3560-73	6.1.4	9485-74	5.12
4204-77	5.12	9651-84	5.5
4461-77	5.12	11701-84	5.5
5632-72	3.1	14019-80	5.10
5639-82	5.8	14192-96	6.1.2
6009-74	6.1.4	19903-74	2.2, 5.3
6032-89	4.3, 5.12	19904-90	2.2, 5.3
6507-90	5.3	21650-76	6.1.4
7502-98	5.3	24597-81	6.1.3
7564-97	5.4	26877-91	5.3

4.

2—92

( 2—93)

5.

1,

1987 .( 10—87)