



25174—82
(2712—80)

S—93

25174—82

Rubber pressure hoses with textile reinforcement.
Parameters and dimensions

(CT 2712—80)

25 5000

01.01.S3

1.

()
,

, , , ,

,
,

2.

(, . 1).

. 1.

(6)
©

, 1982
, 1994

	I	II
3,2 4,0 5,0	±0,50	±0,75
6,3 8,0 10,0 12,5 16,0 20,0	±0,75	±1,00
25,0 31,5	±1,25	±1,50
40,0 50,0 63,0	±1,50	—
80,0 100,0 125,0 160,0 200,0	±2,00	—
250,0 315,0	±3,00	1

1.

I—

:

2.

II—

,

3. 01.01.94

38,0; 65,0; 75,0;

150,0

,

4.

$$\begin{array}{llll}
 \left(\begin{array}{c} / \\ 2 \end{array} \right) & & : 0,10 & (1,00); \\
 0,16 (1,6); & 0,20; (2,00); & 0,25 (2,50); & 0,30 (3,00); & 0,40 (4,00); \\
 0,50 (5,00); & 0,63 (6,30); & 0,80 (8,00); & 1,00 (10,0); & 1,60 (16,0); \\
 2,00 (20,0); & 2,50 (25,0); & 4,00 (40,0); & 5,00 (50,0); & 6,30 (63,0); \\
 8,00 (80,0); & 10,00 (100,0). & & &
 \end{array}$$

5.

. 2.

	/	
	1,25	2,50
	1,50	3,00
	2,00	4,00—5,00
	1,50—2,00	3,00—5,0.0
	2,50—3,00	5,00
	4,00	

(6.

1).

2,

, 4 25174—82

1.

2.

19*03.88

1114

3.

2712—80

4.

5.

(3—93)

6.

(1994 .)
1988 .(10—88)

1,

*5 05 94. , . 15 94 . 0,35 - . 0,35.
- . » 0,25 . 674 - 1423

« » 107076 , 6 , 176