

25676-83

,

,

,

12-2005



2007

25676-83

Rubber rotary drilling hoses. Principal parameters and dimensions, technical requirements, test methods, marking, packing, transportation and storage

MKC 83.140.40
25 5731 0000

22 1983 1273

01.01.84

3-93

(5-6—93)

3350-81

1

11

(L) 3 25 .
01.01.89

3 18

1%

10

+ 1 —
12.

10

13

11

2007

©

6

, 1983
. 2007

			I				II						
						D		1	2	3			
50	$\pm 0,5$	—	—	—	—	—	—	15	20	—	25 5731 0102 05 25 5731 0202 02		
51	—	3	10,5	14	27,5	—	—	15	20	30	—		
63,5	—	3	10,5	14	27,5	34,5	52	15	20	30	—		
65	$\pm 0,5$	—	—	—	—	—	—	15	20	—	25 5731 0103 04 25 5731 0203 01		
76	$\pm 0,5$	4	—	—	27,5	34,5	52	15	20	30	25 5731 0104 03 25 5731 0204 00		
89	—	5	—	—	27,5	34,5	52	15	20	30	—		
100	$\pm 1,0$	—	—	—	—	—	—	15	20	—	25 5731 0105 02 25 5731 0205 10		
102	—	5	—	—	—	—	—	15	20	30	—		

1. 89 4

2.

1.4.

I

1.5.

2.

50; 51 63,5; 65 76 89 100; 102	1000 1200 1200 1400 1400
--	--------------------------------------

2.

2.1.

2.2.

 40° 45° 80°
20%

2.3.

1.4,

2.4.

3.

3.1.

1

3.2.

0,50 /
1 ,

1.4.

0,17

4.

4.1.

(, ;
;);

4.2.

4.3.

4.4.

5°

4.1

10 ° ,

4.5.

. 4

25676-83

1.

$$(\quad) \quad . \quad (\quad)$$

$$\wedge \quad 0,5 \quad - \quad + \quad + \quad /, \quad (1)$$

L_T —

R —

/ —

0,3

(H_s)

$$H_s = 0,5 \quad L_T + Z$$

(2)

L_T —

Z —

0,1

(1),

2.

180°.

160°.

3.

4.

5.

6.

7.

10 %

8.

9.

10.

71 °

06.06.2007. 04.07.2007. 60 84 8-
. 0,93. . . . 0,45. 60 . . . 530.

« » , 123995 , ., 4.
www.gostinfo.ru info@gostinfo.ru
« »
« — . « » , 105062 , ., 6