

;

;

2

;

,

,

12-2005



2007

25736-83

Rubber hoses for automobile pneumatic brakes.  
Principal parameters and dimensions, technical requirements, testing methods,  
marking, packing, transportation and storage, operating rules

MKC 83.140.40  
25 5511

15 1983 . 1894

01.01.84

( 11—95) 7—95

40 ° .

2711—80.

1.

1.1.

1.2.

1.3.

2007 .

©

©

, 1983  
, 2007

	13±0,7 24 102
( ) ,	
, , :	
I	0,63
II	1,0
2.	
2.1.	
2.2.	40° .
2.3.	1
430—77*	50 %.
2.4.	
70 .	
2.5.	+ 3 %.
2.6.	
2.7.	1,5 / .
2.8.	1500 .
2.9.	6,3-
3.	
3.1.	(23+2)° .
3.2.	30
	0,1 .
	0,1
10 .	
+ 10 .	
3.3.	
500 .	
(0,125 + 0,050) /	2.8. —
2 ,	
3.4.	
3.3.	2 ,
2.9,	
3.5.	800 ,
40 °	
70—72 .	
3—5	180° , 10 ,
*	9.030—74 ( ) .

3.6.

430—77

24

70° .

1

3.7.

$$(50 + 5)10^{-8}$$
$$(40 + 3)^{\circ}$$

204

24

70 .

$$(23 + 2)^\circ$$

3.8.

1000

0,07

1

500

3.9.

10

20

180°.

 $+ 0,5$ 

200

$$\frac{(25 + 2)}{50} \%$$
$$).$$

3.10.

$$\frac{(25 + 2)}{500} \quad / \quad .$$

4.

4.1.

 $(\quad);$ 

4.2.

500

300

$$(\quad);$$

. 4      25736-83

4.3.

25° .

5.

5.1.

( , ).

5.2.

1.

85° .

2.
- 1

-

-

,

», 123995 ,  
www.gostinfo.ru info@gostinfo.ru  
« »