



27701—88

8-93

**Cylindrical worm reduction gears.
Basic parameters**

27701—88

41 6151

01.01.89

1.

2144:

40—500 ;

40—250 ;
63—500

, 1. (, . . 1).

2.

2144:

5—100;
80—4000. $\pm 5\%$ — $\pm 8\%$ —

3.

24386.

©

, 1988

©

, 1994

4.

1800 /

3000 /

10 /

5.

=31,5

—1000

—1500 /

1	2	3
22,4	25,0	28
31,5	35,5	40
45,0	50,0	56
63,0	71,0	80
90,0	100	112
125	140	160
180	200	224
250	280	315
355	400	450
500	560	630
710	800	900
1000	1120	1250
1400	1600	1800
2000	2240	2500
2800	3150	3550
4000	4500	5000
5600	6300	7100
8000	9000	10000
11200	12500	14000
16000	18000	20000
22400	25000	28000
31500	35500	40000
45000	50000	56000

1

3—5. (, . 1).

1.

2.

**28.04.88 1201
5836—86** «

»

01.01.89

3.

4.

2144—76
24386—91

1; 2
3

5. 1994 . 1,
1992 .(5—92)

6. 34 20.01.92

17.02 94 . 15.06 94. . 0,23. . 0,23.
- . 0,20 . 633 . 1411.