



**2879—88
(3897-82)**

11-95

Hot-rolled hexagonal steel. Dimensions
(CT)

2879-88
3897-82)

093100; 093200; 093300 *123

01.01.90

1.


8 100 .

2.

—
—

3.

,



©
©

, 1988
, 1997

	,	,	,	1
8	+0,1		0,5542	0,435
9	-0,3		0,7015	0,551
10			0,866	0,680
11			1,048	0,823
12	+0,2		1,247	0,979
13	-0,3		1,463	1,15
14			1,697	1,33
15			1,948	1,53
16			2,217	1,74
17	+0,2		2,503	1,96
18	-0,3		2,806	2,20
19			3,126	2,45
20			3,464	2,72
21			3,822	3,00
22	+0,2		4,191	3,29
24	-0,4		4,993	3,92
25			5,412	4,25
26			5,847	4,59
28			6,790	5,33
30			7,794	6,12
32			8,868	6,96
34			10,010	7,86
36	+0,2		11,220	8,81
38	-0,6		12,510	9,82
40			13,860	10,88
42			15,270	11,99
47			19,040	14,95
48			20,00	15,66
50			21,64	16,99
52	+0,2		23,40	18,40
55	-0,9		26,20	20,58
60			31,18	24,50
63			34,37	26,98
65	+0,3		36,59	28,70
70	-1,0		42,43	33,30
75			48,71	38,24

	,	,		1
				,
				2
80			55,42	43,51
85	+0,4	+0,5	62,57	49,12
90	-1,2	-1,3	70,15	55,07
95			78,16	61,36
100	+0,5	+0,6	86,60	67,98
	-1,5	-1,7		

1.
23; 27; 29; 41; 43; 46; 53; 56; 57

2.
7,85 / 3. 1

3.
26; 27; 28; 29; 30

4.
100

4.

5.
2 6 :

12 . 1,5
6.

+30 — 4 ;
+50 — 4 6 ;
+70 — 6 .
+40 — . 4

7 ;
+5 7 .

. 4

2879-88

7.

()
75 %

()

70 %

32

8.

,

. 2.

2

	,	,
8 14		1,0
. 14 » 25		1,5
» 25 » 55		2,0
* 55		3,0

1,0

, 26

— 30

15—20

1,5

,

60—75

9.

,

. 3.

	I	II
40 . 40	0,5 % 0,4 %	0,5 %

10.

0,2 %

,

11.

1

150

.

12.

4 /

24

		14		14		50
		,		,		
18	,	— 3	/			
		50	— 3			
			/			
15	.					
13.						
		150		1,5		
		250		3,0		
250	.					

. 6

2879—88

1.

, ; . . . , . . . ; . . . (. . .); . . . , . . . , . . . , . . . ; . . .

2.

29.06.88 2557

3.

3897—82

4.

2879-69

5.

4—93

(4-94)

6.

1997 .

021007 10.08.95. 04.03.97. 24.03.97.
0,47. . . 0,37. 298 315. 228.

107076, , ., 14.

— . “ ”
, ., 6