

()

INTERSTATE COUNCIL FOR STANDARDIZATION, METROLOGY AND CERTIFICATION
(ISC)

32590-
2013



2014

32590—2013

1.0—92 «
1.2—2009 «

1

106 «

».

)

«

» (

«

2

3

(63- 23 2013 .)

(03166) 004 - 97	3166)004 - 97 (
	AM KG RU TJ	

4

2013 . 2407-

32590—2013

30

01

2015 .

5

()

«

»,

».

«

».

©

, 2014

Fillings of copper and copper alloys with ends for capillary soldering or capillary brazing to copper tubes.
Specifications

— 2015—01—01

1

*

()

2

8

166—89 (3599—76)
613—79
859—2001
1652.1—77 (1554—76)
1652.2—77 (4749—64)
1652.3—77 (1812—76. 4748—84)
1652.4—77
1652.5—77 (4751—84)
1652.6—77
1652.7—77
1652.8—77
1652.9—77 (7266—84)
1652.10—77
1652.11—77 (4742—84)
1652.12—77
1652.13—77
1953.1—79
1953.2—79
1953.3—79
1953.4—79
1953.5—79
1953.6—79
1953.7—79
1953.8—79
1953.9—79
1953.10—79
1953.11—79
1953.12—79

1953.13—79				
1953.14—79				
1953.15—79				
1953.16—79				
2768—84				
2991—85			500	
3282—74				
3560—73				
4461—77				
6507—90				
7376—89				
9557—87			800x1200	
9716.1—79				
9716.2—79				
9716.3—79				
9717.1—82				
9717.2—82				
9717.3—82				
10198—91			200	20000
10354—82				
13938.1—78				
13938.2—78				
13938.3—78				
13938.4—78				
13938.5—78				
13938.6—78				
13938.7—78				
13938.8—78				
13938.9—78				
13938.10—78				
13938.11—78				
13938.12—78				
13938.13—93				
13938.15—88				
14192—96				
15102—75				
5.0				
15527—2004			()
15846—2002				
21646—2003				
21650—76				
22225—76			0.625	1,25
24231—80				

24597—51
25086—2011
26663—85

28057-89
-2013

3

3.1

3.2

4

4.1

D				
	-	,	-	-
6.0				
8.0				
9.0				
10.0				
12.0	+ 0.15		+ 0.04	
14.0	+ 0.06		• 0.05	
14.7				
15.0				
16.0				
18.0				
21.0				
22.0	+ 0.18		+ 0.05	
25.0	+ 0.07		• 0.06	
27.4				
28.0				
34.0				
35.0				
40.0	+ 0.23		+ 0.06	
40.5	+ 0.09		• 0.07	
42.0				
53.6				
54.0				
64.0				
66.7				
70.0				
76.1	+ 0.33		+ 0.07	
80.0	+ 0.10		• 0.08	
88.9				
106.0				
108.0				
133.0	+ 0.70		+ 0.20	
159.0	+ 0.23		• 0.20	

1

34.0 108.0

2

133.0 159.0

(-)

()


.1 .2 (1.).

.1 .2 ()

4.2

4.3

1.



1- ;2- : - :L?- - ,

1-

4.4

()

()

2.

2

8

	()		(L.L.)
	L-	L -	
6.0	5.8	7.8	±1.2
8.0	6.8	8.8	±1.2
9.0	7.8	9.8	±1.2
10.0	7.8	9.8	±1.2
12.0	8.6	10.6	±1.4
14.0	10.6	12.6	±1.4
14.7	10.6	12.6	±1.4
15.0	10.6	12.6	±1.4
16.0	10.6	12.6	±1.4
18.0	12.6	14.6	±1.4
21.0	15.4	17.6	±1.4
22.6	15.4	17.6	±1.6
25.0	16.4	18.4	±1.6
27.4	18.4	20.4	±1.6
28.0	18.4	20.4	±1.6
34.0	23.0	25.0	±1.6
35.0	23.0	25.0	±2.0
40.0	27.0	29.0	±2.0
40.5	27.0	29.0	±2.0
42.0	27.0	29.0	±2.0
53.6	32.0	34.0	±2.0
54.0	32.0	34.0	±2.0
64.0	32.5	34.5	±2.0
66.7	33.5	36.5	±2.0
70.0	33.5	36.5	±2.0
76.1	33.5	36.5	±2.5
80.0	35.5	38.5	±2.5
88.9	37.5	40.5	±2.5
106.0	47.5	51.5	±2.5

	()		(L, U)	
	()			
	U			
108.0	47.5	51.5	±2.5	
133.0	53.5	56.0	±2.5	
1S9.0	63.5	59.5	±2.5	

4.5 ()

3.

	()		(L, U)
	1<	L-,	
14.7	7.0	9.0	±1.4
15.0	7.0	9.0	±1.4
16.0	7.0	9.0	±1.4
18.0	7.0	9.0	±1.4
21.0	8.0	10.0	±1.4
22.0	8.0	10.0	±1.6
25.0	8.0	10.0	±1.6
27.4	9.0	11.0	±1.6
28.0	9.0	11.0	±1.6
34.0	10.0	12.0	±1.6
35.0	10.0	12.0	±2.0
40.0	10.0	12.0	±2.0
40.5	10.0	12.0	±2.0
42.0	10.0	12.0	±2.0
53.6	11.0	13.0	±2.0
54.0	11.0	13.0	±2.0
64.0	11.0	14.0	±2.0
66.7	11.0	14.0	±2.0
70.0	12.0	15.0	±2.0
76.1	12.0	15.0	±2.5
80.0	13.0	16.0	±2.5
88.9	14.0	17.0	±2.5
106.0	15.0	19.0	±2.5
108.0	15.0	19.0	±2.5
133.0	19.0	24.0	±2.5
159.0	21.0	26.0	±2.5

4.6

4.

D		D	
6.0	4.0	35.0	29.0
8.0	6.0	40.0	35.0
9.0	7.0	40.5	36.0
100	7.0	42.0	36.0
12.0	9.0	53.6	47.0
14.0		54.0	47.0

4

14.7	11.0	84.0	55.0
15.0	11.0	68.7	57.0
16.0	12.0	70.0	60.0
18.0	14.0	76.1	65.0
21.0	18.0	80.0	68.0
22.0	18.0	88.9	76.0
25.0	21.0	106.0	92.0
27.4	23.0	108.0	92.0
28.0	23.0	133.0	113.0
34.0	29.0	159.0	135.0

4.7

4.8

5.

8

6.0	0.6	1.0	1.0
8.0	0.6	1.0	1.0
9.0	0.6	1.0	1.0
10.0	0.6	1.0	1.0
12.0	0.6	1.1	1.1
14.0	0.6	1.1	1.1
14.7	0.7	1.2	1.2
15.0	0.7	1.2	1.2
16.0	0.7	1.2	1.2
18.0	0.8	1.4	1.4
21.0	0.9	1.4	1.4
22.0	0.9	1.4	1.5
25.0	0.9	1.4	1.6
27.4	0.9	1.5	1.6
28.0	0.9	1.5	1.8
34.0	1.0	1.6	1.8
35.0	1.0	1.6	1.8
40.0	1.1	1.8	2.0
40.5	1.1	1.6	2.0
42.0	1.1	1.8	2.0
53.6	1.2	1.9	2.3
54.0	1.2	1.9	2.3
64.0	1.4	2.0	2.4
66.7	1.4	2.0	2.4
70.0	1.4	2.3	2.6
76.1	1.6	2.6	2.8
80.0	1.8	2.8	2.9
88.9	1.8	2.9	3.1
106.0	2.1	3.3	3.5
108.0	2.1	3.3	3.5
133.0	2.3	4.2	4.5
159.0	2.6	5.2	5.5

32590—2013

— XX;
 5001 : 22 1 5001 ...
 1 15 5130R: 22 15 22
 15x22 1 5130R ...
 5001 : 22 2 5001 ...
 5
 5.1
 5.2 : 1 1 2 859. Cu-DHP
 Pb2As : ; 59-1. 58-3 15527. CuZn39Pb3,
 7: 05 5 5

6 »		Cu-DHP		r/cw ^J
		+	%	
Cu-DHP		99.90"	0.015 0,040	*8.9
	0.015 %			

7 -

CuZn39Pb3, CuZn36Pb2As

		% -										- r/CM ^J
		-	-	-	-	-	-	-	-	-	-	
2 39		57.0 59.0	0.05	-	0.3	-	0.3	2.5 3.5	0.3	-	0.2	8.4
Cu2n36P b2As		61.0 63.0	0.05	0.02 0.15	0.1	0.1	0.3	1.7 2.8	0.1	-	0.2	8.4

8 -

CuSnSzn5PbS-C

		% -											
		-	-	-	-	-	-	-	-	-	-	-	-
CuSn52n5P 5		83.0 87.0	2.0	0.10	4.0 6.0	4.0 6.0	4.0 6.0	0.01	0.3	0.10	0.25	0.01	-

5.3

15527.

5.4

5.5
)

5.6

1 / 2.

5.7

5.6

10 %

5.9

5.10

6

6.1

-

-

-

6.2

300

32590-2013

6.3

6.4

6.5

6.6

6.7

6.8

6.9

6.10

7

7.1

7.2

.1 .1 ().

7.3

.2 .2 ().

7.4

6507.

7.5

166.

7.6

7.7

3.75 54 — 108
15

6 0.75 54 —

.2,4 — 106

(.1).

0.5

3.75

7.8

7.9

24231.

13938.1 - 13938.13,

13938.15. 9717.1 - 9717.3.

13938.1 - 13938.13. 13938.15. 1652.1 - 1652.13.
9716.1 - 9716.3. 1953.1 - 1953.16. 25086.

7.10

21646 pH 9.5

7.11 28057.

• - 200
 • - 200 400
 7.12

8 , ,

8.1

• - CR DRA;
 • - DRB.

8.2

8
 • 2991, 10198:
 • 15102. 22225;
 • 3282:
 • 9557;
 • 3560;
 • 7376;
 • 10354.

8.3

8.4 14192

«

8.5 15846.

8.6 26663.

24597.

21650.

- 5000

1250

9557

50x50
 0,3x30

3

8.7

()

32590—2013


•
•
8.8

8.9

9

9.1

()




3.2

.1 -

.1 -

<i>D.</i>	<i>di</i>		<i>d₁</i>		<i>di</i>
6	6.037		5.950		6.050
8	8.037	+ 0.003	7.950	+ 0.003	8.050
9	9.037		8.950		9.045
10	10.037		9.950		10.050
12	12.036		11.950		12.050
14	14.036		13.950		14.050
14.7	14.736	+ 0.003	14.650	+ 0.003	14.750
15	15.036		14.950		15.050
16	16.036		15.950		16.050
18	18.036		17.950		18.050
21	21.045		20.940		21.060
22	22.045		21.46		22.060
25	25.045	+ 0.004	24.940	+ 0.004	25.060
27.4	27.445				27.460
28	28.045		27.940		28.060
34	34.054		33.930		34.065
35	35.054		34.930		35.065
40	40.054	+ 0.004	39.930	+ 0.004	40.065
40.5	40.554		40.430		40.565
42	42.054		41.930		42.070
53.6	53.653	+ 0.005	53.530	+ 0.005	53.665
54	54.053		53.930		54.065
64	64.063		63.020		64.060

1					
	, <i>di</i> .		, <i>d_j</i> ,		, <i>di</i> .
66.7	66.763		66.620		66.780
70	70.063	+ 0.005	69.920	+ 0.005	70.180
76.1	76.163		76.020		76.180
80	80.062		79.920		80.080
88.9	88.962	+ 0.006	88.820	+ 0.006	88.980
106	106.062		105.920		106.080
108	108.062		107.920		108.080
133	133.120	+ .	132.650	+ .	133.200
159	159.1S0		158.650		159.200



3.2

.2 -

.2-

			, di.			
				-	-	,
				dr.		
6	6.068	-0,003		6.156	-0,003	0,7
	8.068		8.060	8.150		
9	9.068		9.060	9.150		
10	10.068		10.060	10.150		
12	12.6&	-0,003	1\$	12.150	-0,003	0,7
14	14.069		14.060	14.150		
14.7	14.769		14.760	14.850		
15	15.069		15.060	15.150		
16	16.069		16.060	16.150		
18	18.069		18.060	18.150		
21	21.080	-0,004	21.070	21.180	-0,004	1,0
22	22.080		22.070	22.180		
25	25.080		25.070	25.180		
27.4	27.480		27.470	27.580		
28	28.080		28.070	28.180		
34	34.096		34.090	34.230		
35	35.096		35.090	35.230		
40	40.096		40.090	40.230		
40.5	40.596		40.590	40.730		
42	42.096		42.090	42.230		
53.6	53.697	-0,005	53.690	53.830	-0,005	
54	54.097		54.090	54.230		
64	64.108		64.100	64.330		1,5
66.7	66.808		66.800	67.030		
70	70.108		70.100	70.330		
76.1	76.208		76.200	76.430		
	80.108	-0,006	80.100	80.330	-0,006	2,0
88.9	69.008		89.000	89.330		
1			106.100	106.330		
108	108.108		108.100	108.330		
133	1&2	-0,008	133.230	133.700	-0,008	2,5
159	159.238		159.230	159.700		

()

<u>.1</u>			
		-	
1		4180	
2		4221	*5
3	90*	5001	

.1

90*

5001L

^-^-

90'

5002

90*

5002L

45*


5040




8	45*	5041	JL
9	180*	5060	
10		5085	
11		5086	

5.1

		-	
12	90*	5090	
13	90*	5092	
14		5130	
15		5131	

		1	
16		5240	
18		5243L	1V
			J
17		5243	
19		5270	
			•
			£ ^

5.1

		-	
20		5270S	
21		5290	
22	•	5301	
23	:	51	

Номер по порядку	Наименование фитинга	Базовоеко- довое об- значение фитинга	Рисунок
24	Отвод 90° для высокотемпературной пайки	ЗКМ	
25	Отвод 45° для высокотемпературной пайки	КМ	

()

Ta_6ji_M_ifaBJ;^Kcnn^aTaunoHHue^ewEpaT^fa_MjiaBJieK*te

-		-	-					
			6	34	.34	54	.54	106
()	50-0.5 40-2	30	1.6	1.6	1.6	1.0		
		65	1.0	1.0	1.0	0.6		
		110	0.6	0.6	0.6	0.4		
	1-0.5	30	2.5	2.5	2.5	1.6		
		65	2.5	2.5	1.6	1.6		
		110	1.6	1.6	1.0	1.0		
()	65. 45 45-15-16-24. 40	30	2.5	2.5	2.5	1.6		
		65	2.5	2.5	1.6	1.6		
		110	1.6	1.6	1.0	1.0		

1
2

(}

T^enjj^ua^J^^Kcnn^arai^oHwejeMnegaT^ajiMeneHMe

		- - - «	1	, , , , ,				
				34	14.7	34	54	54
()	65. 45	30	2.5	2.5	2.5	1.6	1.6	0.5
	45-15-16-24. 40	65	2.5	1.6	1.6	1.6	1.6	0.3
	-4- .	110	1.6	1.0	1.0	1.0	1.0	0.2

1
2

()

.1

.2

/


.3.1

.2

.3.3

.4

100



1
2
3
4
5

.1-

.5

32590—2013

().

()

.1

.1.1

10^{-2}

4461

.1.2

2768.

8

.2

.2.1

25 % • (v/v)

.2.2

5

()

o*ⁱ

.1

.1.1

().

.2

.2.1

.2.1.1.

()

.2.1.2.

.2.1.1

.2.2;

•

.2.3;

•

.2.4;

•

.2.5.

•

.2.2;

•

.2.4;

•

.2.3;

•

.2.5.

.2.1.2

.22;

•

.2.4;

•

.2.5.

.2.2

.2.2.1

10

*

.2.3

.2.3.1

5

2

30

8

.2.4

.2.4.1

.2.4.2

.2.4.2.1

30
2-3

50 % (v/v)

80

.2.5

.2.5.1

•
•
•

S.

10

)

S= 7 * (1 * L

(.1)

d-
L -

6)

p-t

(.2)

, , , / 1;
(- , ,

)

(),

(, ,)

()

((,)).

.2.5.2

10 2.

.2.5.3

10

(, 10 *)

.3.1
99.995 %.

) 99.995 %.
1) (450 500 ,
2) ,
3) :
} (600 ,
) 750 .

.4

.4.1

(.4.2);

•

(.4.3);

•

(

(.4.4).

),

8

.4.5.

.4.2

.4.2.1

(())

0.01 / *

.4.3

.4.3.1

()

0.02 / *

.4.4

.4.4.1

().

0.01 /

.4.5

.4.5.1

10 :
• 50 % - (v/v)
30 ,

80 , : 2-3

0.1 :

.4.2, .4.3 .4.4.

0.02 / %

.5

.5.1

(/ %).

.6.1

32590—2013

669.3-462:006.354 23.040.15 64 18 4450

01.09.2014. 60x84V₈.
4,19. 37. 3401

« 123995 »
www.gostinfo.ru .. 4.
info@gostinfo.ru

федеральное агентство
по техническому регулированию
и метрологии

федеральное агентство
по техническому регулированию
и метрологии

федеральное агентство
по техническому регулированию
и метрологии