



6008—90

(497—89)

199/06—8 eg

• " * 02

6008—90

Metallic manganese and nitrated manganese
Specifications

(CT 497—89)

08 3400

01.07.91
01.07.96

- 1.
- 1.1.
- 1.2.
- 1.2.1.
- . 1.

		, %					
			-				-
998 9 97	-	99,8 99,7	0,04 0,06	—	0,003 0,005	0,03	—
965 95	- -	96,5 95.0	0,20	0,8 1,8	0,05 0,07	0,05 0,05	
92 6	- - -	92,0		—	0,005		6,0
87 6 \$9 4 91 2	- - -	87.0 89.0 91,0	0.20 0,20 0,20	1.8 1,8 1,8	0,07 0,07 0,07	0,05 0,05 0,05	6.0 4.0 2,0

1.2.2. -

0,13% 95. 0,6% 1,3%, 965;

1.2.3.

998 997 ()

965, 2x2 95 —, 5% 15 3% ;

10X10 92 6 —, 10% ;

15 5x5 87 6, 89 4, 91 2 — 10% ; 15 .

10 20% .

1.2.4. -

,

.

-

965 95.

1.2.5.

1.2.5.1.

-

12.1.007.

1.2.5.2.

,

.

,

-

—

-

1.2.5.3.

()

-

 $0_2-0,3 / 3$

-

12.1.005.

.

1.2.5.4.

12.1.007

,

.

1.2.5.5.

,

-

6-

.

-

1.2.5.6.

()

:

 $90 / 3$ —

;

 $1000 / 3$ —

(t .)

:

240° —

;

620° —

.

—

12.1.044.

1.3.

—

26590

:

-

-

-

,

.

965

95

. 2

2.

2.1.

-

.

()

.

998, 997, 92 6 , *

2,5%. 2,0%, 95, 87 , 965 89 4, 91 2 — *

2.2. —

26999.

2.3. —

2.4. —

22310.

2.5. —

998, 997 92 6 —

«965, 95, 87 6 89 4, 91 2 —

2.6. 998 997 87 6, 89 4, 91 2 — 965,

95 —

2.7.

3.

3.1. 26999

3.2.					-
27041,	16698.1,	16698,4,	28473, 16698,5,	27069, 16698.13	
		,			
3.3.		22310		,	-
3.4.					
3.5.					
	<				
			—	26590	-
:					
				,	-
				,	-
			,		-
			—		-
					-
,				,	

* ()

2

		/ 8'	- / 3'	- / 3'	- / 3	1', -
* >	-	0,3	0.01	0 001	0,1	1503
0 ₂	-					3 2
0 ₂	-	0,05				1

1.

· · · , · · · , · · ·

2.

17.12.90 3150

3.

— 1996 .
— 5 .

4.

6008—82

5.

497—89

6.

-

-

	12 1 005—88	12 5 3	
	12 1 007—76		1 2 5 1 ; 1 * 2 5 4
	12 1 044—89		1 256
	166 8 1—71		3 2
	16698 4—71		3 2
	16698 5—71		3 2
IOCT	16698 13—84		3 2
	22310-84		2 4 , 3 3
1	36590—85		1 3 , 4
	26999—86		2 2 ,
10	27041—86		3 2
	27069—86		3 2
	28473-90		3 2

6000 . 03 0191 » nfew 91 0,5 0,5 .- 0,39 - 20 .

« » « » , 123557, , , 6' 4 ., 3