


7676-73

Steel wire ropes. Locked conveying wire rope with two layers of V-shaped wire, one layer of Z-wire and type TK core. Dimensions 12 5100, 12 5200

01.01.75

1.

1+6+12, 1+6+12+18 1+6+12+18+24.



2.

												, (), , / 2 (/ 2)							
			1-			2-						100							
50,0	3,6	19	5	18	17,8	5	24	19,2	6	24	30,8	1713,80	1469,51	2010 (205500)	2180 (222500)	2345 (239500)	2515 (257000)	2685 (274000)	2850 (291000)
52,0	4,0	19	5	19	17,8	5	26	19,2	6	25	30,8	1846,16	1582,83	2170 (221500)	2350 (240000)	2525 (258000)	2705 (276500)	2890 (295000)	3070 (313500)
54,0	4,4	19	5	20	19,0	5	27	19,2	6	26	30,8	1988,10	1704,37	2335 (238500)	2525 (258000)	2720 (278000)	2920 (298000)	3115 (318000)	3305 (337500)
55,0	3,4	37	4,5	21	17,2	5	27	19,2	6	26	30,8	2016,33	1728,06	2365 (241500)	2565 (262000)	2760 (282000)	2955 (302000)	3160 (322500)	3355 (342500)
60,0	4,1	37	4,5	24	17,2	5	30	20,1	6	28	32,3	2408,69	2063,60	2830 (289000)	3065 (313000)	3300 (337000)	3535 (361000)	3770 (385000)	4005 (409000)
65,0	3,1	61	4,5	26	18,3	5	33	20,1	6	30	32,3	2763,97	2367,31	3245 (331500)	3515 (359000)	3785 (386500)	4060 (414500)	4330 (442000)	4600 (469500)
70,0	4,3	61	4,5	30	18,3	5	33	22,5	6	37	28,5	3231,84	2767,12	3795 (387500)	4115 (420000)	4425 (452000)	4745 (484500)	5065 (517000)	5380 (549000)

1, (, . 2).

2,

3,

1370 / 2 (140 / 2)

01,01,91.

60,0 , 1,

1270 / 2 (130 / 2):

60, - 0 7*76-75

(, , 1,2),

*76*76—*73 . 2

.3 7676-73

3. — , , , , , , -
18899.

1.

2.

15.06.73 1484

3.

7676-55

4.

-

18899-73

3

5.

4-93

-

(4-94)

6.

1, 2,

1985 .,

1989 . (6-85,

3-90)