



8407 — 89

12-89/1*1*

3

Reused rubber raw materials.
Tyres and inner-tubes. Specifications

8407—89

25 2120

01.01.91
.01.96

1.

1—
2—

3 —

(£)

, 1990

I

9,35-15	21,00-28* **;	16,0-20;	1600X600-685*;	18,00 24 ;
9,00-10	20,5-25*;	15,5-38;	1500x600-635;	16,00-24;
8,40-15	28,1 R26*;	15,5R38;	1300x530-533;	16,00-20;
8,25-15	28,1-25*;	12,4R28;	1220X560-533;	15,00-20;
8,20-15	23,1-26*;	12-16;	1200x500-508;	14,00-20;
9,00-20	23,1 R26*;	11,2-42;	1150x420-457;	14,00-24;
8,25-20	21,3-24;	11,2-20;	1025X420-457;	13,00-20;
7,50-20	21,3R24i	11,2-16;	830X240-381,	12,00-20;
6,50-2	18,4R34;	13,6R38;	1300X750*;	11,0-20;
8,30-20	18,4-30;	340-457*;	1300X700 *;	10,00-20;
9,5-42;	18,4-24;	320-457;	1140X700";	15,5/65-18;
9,5-32;	16,9R38;	280-457;	1140x600",	16,5/70-18;
9, 3 6;	16,9R30;			310/80-5 08P;
14,9/13-30;	13,6/12-38;	12,4/11-38;	11,2/10-28;	

*

**

1.
2 ,
3-
3.

3-

2	3			
,	,	,	,	
5,50-16, 5,00 10, 4,50-10, 4 00-16; 4,00-10, 4,50-9; 6,50-20, 6,00-16, 5,00-16, 7,10-15, 7,00-15, 6,70-15; 6,45-15, 6,40-15,	6 50-15, 6,40-13; 6,30-13; 6,00-13, 5,90-13; 5,20-13; 5 20-10, 185/82R-15; 185/80R-15, 165382R-15, 175-16/6, 95-16; 185-14/7, 35-14; 175 13/6,95 13, 165 13/6,45 13, 155 13/6, 15 13,	21,00 33***, 18,00 -25***, 2,5 /85-16; 6,70-10, 4,00-10, 3,75-10, 3,25-16, 3,25-19, 3,00-18, 2,25-19, 4,00-17, 3,00-10,	12 00R20 370/80R508 11.00R20 10,00R20 3,75-19; 3,75-18; 3,00-19, 3,50-5; 2,50-19; 4,00-18; 3,50-18,	205/70R 175/8DR-13 175/70R-13 165/80R-13 165/70R-13 165/80R-14 175/70R-14 155/70R-13 135/SDR 13

2.

,

3.

1 2-

3-

4.

,

1200

5.

,

6.

,

,

,

,

,

,

,

7.

,

,

8.

,

9.

15—30

10.

—

14192

,

,

,

11.

,

12.

1.

— . . ; . . . ; . . . ; . . . ; 3. . . —

2.

14.12.89 3732

3.

— 1994,

—

3

4.

8407—84

5.

,

14192—77

10

10	04 01 90	20 02 90 0 5	, 0,5	, 2"	3
	«	»	, 123557,	, . 6 , . 1590	. 3
	.. «	» ..			