

8786-68

Cold-drawn steel for Woodruff keys. Dimensions

8786-58


22

1968 .

01.07.71

23.05.90 1268

1.



0.025 D.

| <i>h</i> | <i>D</i> | <i>t</i> | <i>1</i> |
|----------|----------|----------|----------|
| 1.4      | 4        | 3.8      | 0,031    |
| 2.6      | 7        | 6.8      | 0.102    |
| 3.7      | 10       | 9.7      | 0.207    |
| 5.0      | 13       | 12,6     | 0.369    |
| 6.5      | 16       | 15.7     | 0.602    |
| 7.5      | 19       | 18.6     | 0.818    |
| 9        | 22       | 21.6     | 1.15     |
| 10       | 25       | 24.5     | 1.44     |
| II       | 28       | 27.3     | 1.76     |
| 13       | 32       | 31,4     | 2.41     |
| 15       | 38       | 37,1     | 3.23     |
| 16       | 45       | 43,1     | 3,99     |
| 17       | 55       | 50.8     | 4,52     |
| 19       | 65       | 59.1     | 6.22     |

*I, 2*,  
( 5—80, 7—84).

1980 .

1984 .

= 10      :      .      .      .      .      .  
(      —      ,      .      .      1, 2).      .      .  
2.      .      .  
3.      .  
-       $h$       h9;  
-       $d_x$       h12.  
(      .      .      1).

8786-68  
60      /      2.